



Cordless LED Flashlight







Multifaceted reflector enables to illuminate evenly and Zoom function



Multifaceted reflector enables to illuminate evenly







Entire circle is in uniform brightness

Zoom function



12 position pivoting flashlight head



Strap hook



ML106

Continuous illumination (approx) on a single full battery charge: hours

12V/max CXT	
BL1016	5
BL1021B	6
BL1041B	12

Magnet attachment nut for optional magnet attachment


Part No. GM00001683(EU) Part No. GM00001714






(ML106 Only)











Cordless LED Flashlight

ML106 12V max / DML808 18V, 14.4V

ML106 Run Time (hrs) Luminous flux Up to: 12 190 lm at 1m from the light source 170 - 4,500 lx w/BL1016/BL1021B: Illuminance Dimensions 271x66x93 mm (10-5/8"x2-5/8"x3-5/8") w/BL1041B: $(L \times W \times H)$ 290x66x93 mm (11-3/8"x2-5/8"x3-5/8") 0.61 - 0.78 kg (1.3 - 1.7 lbs)

Battery & Charger Sold Separately Standard Equipment: Strap Hook

Net weiaht

DML808



Up to: 32 190 lm at 1m from the light source 170 - 4,500 lx w/BL1815N/BL1820B: 280x79x101 mm (11"x3-1/8"x4") w/BL1830B/BL1840B/BL1850B/BL1860B: 297x79x119 mm (11-3/4"x3-1/8"x4-11/16") 0.73 - 1.09 kg (1.6 - 2.4 lbs)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest $combination, according \ to \ EPTA-Procedure \ 01/2014, are \ shown \ in \ the \ table.$ Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan