



Driver Drill / Hammer Driver Drill DF0300 10 mm (3/8") / HP0300 10 mm (3/8")



Photo: DF0300

Max lock torque

42 N·m

Excellent usability and compact

Driver Drill
DF0300



Hammer
Driver Drill
HP0300



Max lock torque

42 N·m

Compact overall length

DF0300: 220mm, HP0300: 235mm

2 sleeve keyless Drill chuck allows for easy bit installation/removal by one hand.

Capacity of drill chuck 1.0 - 10 mm (1/32 - 3/8")

20 Torque settings



Variable speed control by trigger

Mechanical 2-speed gearing

High / Low: 0 - 1,500 / 0 - 450



Ergonomic handle with soft grip for driver-drill applications



Hammer Driver Drill
HP0300



Driver Drill
DF0300



Accessory

Hook set

Part No. 194759-0



Bit holder

Part No. 452947-8



Driver Drill	DF0300 10 mm (3/8")
Hammer Driver Drill	HP0300 10 mm (3/8")

	DF0300	HP0300
Double Insulation	320W	320W
Variable Speed	Steel / Wood: 10 / 28mm (3/8" / 1-1/8")	Concrete / Steel / Wood: 8 / 10 / 28mm (5/16" / 3/8" / 1-1/8")
Reversing	1.0 - 10 mm (1/32 - 3/8")	1.0 - 10 mm (1/32 - 3/8")
Mechanical 2-Speed	No Load Speed (RPM) Blows Per Minute (BPM)	No Load Speed (RPM) Blows Per Minute (BPM)
Keyless Chuck	High / Low: 0 - 1,500 / 0 - 450	High / Low: 0 - 1,500 / 0 - 450
Torque Setting 20	-	High / Low: 0 - 22,500 / 0 - 6,750
	Max Fastening Torque	Hard / Soft: 56.0 / 21.0 N·m (500 / 190 in.lbs.)
	Max lock torque	Hard / Soft: 56.0 / 21.0 N·m (500 / 190 in.lbs.)
	Vibration Level	42.0 N·m (370 in.lbs.)
		2.5 m/s ² or less
	Sound Pressure Level	Impact Drilling into Concrete: 12.5 m/s ²
	Sound Power Level	Drilling into Metal: 2.5 m/s ² or less
	Dimensions (L x W x H)	82 dB(A)
	Net weight	93 dB(A)
	Power supply cord	235x67x206 mm (9-1/4"x2-5/8"x8-1/8")
		1.2 kg (2.7 lbs.)
		1.3 kg (2.8 lbs.)
		2.5 m (8.2 ft)
		2.5 m (8.2 ft)

Standard Equipment : Bit

Weight according to EPTA-Procedure 01/2014
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201907