



Smooth cutting



Short overall length: 447mm



For added

durability

Longer 30 mm (1-3/16") stroke

for faster cutting performance



Soft grip handle provides increased comfort on the job.



allows to hang the machine on ladder rungs or guard rails of aerial work platform. (country-specific)

Makita 🛈



Toolless blade change

for fast blade installation and removal











Double Insulation Variable Speed Capacity Carrying Case Vibration Level

Standard Equipment: Recipro Saw Blades

Recipro Saw

JR30511 Continuous Rating Input 1.200W Length of Stroke 30 mm (1-3/16") Strokes Per Minute (SPM) 0 - 3,000 U-3,000
Pipe: 130 mm (5-1/8")
Wood: 255 mm (10")
Cutting Boards: 19.5 m/s²
Cutting Wooden Beams: 19.5 m/s² 88 dB(A) 99 dB(A) Sound Pressure Level Sound Power Level Dimensions (L x W x H) 447x97x176 mm (17-5/8"x3-13/16"x6-15/16") Net weight
Power Supply Cord 3.2 - 3.3 kg (7.1 - 7.3 lbs.) 2.5 m (8.2 ft)

The weight may differ depending on the attachment(s). The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

303