



# Cordless Hedge Trimmer

UH020G 500mm (19-3/4")

UH021G 600mm (23-5/8")



# 40V Li-ion max



Lightweight and compact enough to handle easily,  
yet capable of high power trimming



Run time\*  
UH020G /UH021G

**110 / 105 min**

Battery: BL4040

Strokes per minute

**4,200 min<sup>-1</sup>**

Net weight  
UH020G /UH021G

**3.0 / 3.1 kg**

Battery: BL4020



\*Continuous run time (approx) on a single full battery charge (under no-load)



# High efficiency, High durability, High power

## Smooth and efficient trimming

- The output power and number of strokes have been increased compared with our 18V models, achieving smooth and efficient trimming.
- Constant speed control suppresses rotation drop to enable stable trimming.



## Blade type

Single-sided blade with obliquely-angled and triple-ground teeth



With excellent branch introduction and a design that prevents branches from escaping, the blades smoothly capture branches, allowing for trimming without letting branches escape.



Photo: UH020G

UH020G Blade length: 500mm  
UH021G Blade length: 600mm

## Lightweight design

The guide bar is made of aluminum to make the front of the tool lighter for reducing user fatigue.

## Highly durable crank mechanism

Increased crank wall thickness can:

- reduce the chance of falling off of the blade from the crank.
- increase the contact area the blade, reducing wear of the crank.




## Chip receiver (option)

smoothly takes in branches and leaves


- Smooth shape for excellent collection



- Leaves and branches are less likely to fall and slip



Less likely to fall



Less likely to slip


## Redesigned, easy-to-press switch lever

can be pressed without gripping the front handle deep in your palm, allowing for easy control.



## Reverse function to clear jams

When the shear blades are jammed with branches, the shear blades are reversed for a moment to clear the jam by pressing the Reverse button and then pulling the trigger.



LED

Reverse button to clear jams

## Accessories

Model No.	Shear blade set	Blade cover	Chip receiver	Grease vessel set
UH020G (500mm)	1914G4-7	413L91-8	1910T1-0	199450-5
UH021G (600mm)	1914G5-5	413L92-6	1910T2-8	

## XPT / IPX4 -compatible

High water-resistance allows the user to operate the tool even if it is wet with water.

## Charging Time

	Fast Charging	
	DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

\*1 Recommended battery

## Cordless Hedge Trimmer

### UH020G 500mm (19-3/4") UH021G 600mm (23-5/8")

	UH020G	UH021G
Brake	500 mm (19-3/4")	600 mm (23-5/8")
Constant Speed	30.0 mm (1-3/16")	30.0 mm (1-3/16")
Grass Tangle Removing Function	20.0 mm (13/16")	20.0 mm (13/16")
Anti-restart function	4,200 min <sup>-1</sup>	4,200 min <sup>-1</sup>
Standard Equipment : Blade cover, Chip receiver, Battery, Charger	Continuous use	w/BL4040: 110 min
	Guaranteed sound power level*	w/BL4040: 105 min
	Sound pressure level*	83 dB(A)
	Noise K factor*	3 dB(A)
	Measured sound power level*	91.0 dB(A)
	Guaranteed sound power level*	93 dB(A)
	Vibration level *	2.5 m/s <sup>2</sup> or less
	Vibration K factor*	1.5 m/s <sup>2</sup>
	Dimensions (L x W x H)	w/BL4040: 929 x 207 x 185 mm (36-1/2 x 8-1/8 x 7-1/4")
	Net weight**	3.0 - 4.2 kg (6.6 - 9.3 lbs.)
	Net weight (Battery)	BL4020 - BL4080F

The weight may differ depending on the attachment(s), including the battery cartridge.  
Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



PRINTED IN JAPAN 202407

www.makita.com