

**Shear Wrench series**

**6924N**  
M22 (7/8") / M24 (1") / SHTB22  
1,100 N·m  
AC



**6922NB**  
M16 (5/8") / M20 (3/4") / M22 (7/8")  
804 N·m  
AC



**DWT310**  
M16 (5/8") / M20 (3/4") / M22 (7/8")  
804 N·m  
18V x2



**Impact Wrench series**

**TW001G**  
3/4" (19 mm)  
1,800 N·m  
40V max



**TW007G**  
**TW008G**  
1/2" (12.7 mm)  
760 N·m  
40V max



**TW004G**  
**TW005G**  
1/2" (12.7 mm)  
350 N·m  
40V max



**DTW1001**  
3/4" (19 mm)  
1,050 N·m



**DTW700**  
**DTW701**  
1/2" (12.7 mm)  
700 N·m  
18V



**DTW300**  
**DTW301**  
1/2" (12.7 mm)  
330 N·m  
18V



**Accessories**

**Sleeve size reference table**

\* Type F (for HEXA TECH (GFD France))  
\*\* for Chinese market



Bolt Size	Outer sleeve			Inner sleeve		Bolt Size	Outer sleeve			Inner sleeve	
	Hex (mm)	L (mm)	Part No.	L (mm)	Part No.		Hex (mm)	L (mm)	Part No.	L (mm)	Part No.
M16	27	35	764362-7	36	764416-0	M22, 7/8"	36	39	153909-6	39	764418-6
		81	764367-7	82	*764421-7			39	*764423-3		
		100	764406-3	100	764356-2			85	764352-0		
		200	764407-1	200	764400-5			100	764354-6		
		200	764407-1	200	764401-3			170	764354-6		
M20	32	37	764361-9	38	764417-8	200	764411-0	200	764405-5		
		37	**196276-6	38	764417-8	35	764362-7	36	764420-9		
		37	764361-9	38	*764422-5	37	764361-9	38	764419-4		
		83	764363-5	84	764357-0	83	764363-5	84	764353-8		
		100	764408-9	100	764402-1	168	764366-9	169	764355-4		
		200	764409-7	200	764403-9						

**Charging Time**

Battery	Fast Charging	
	DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
*1 BL4050/F 5.0Ah	50 min	85 min

\*1 Recommended battery

Cordless Shear Wrench	
WT001G M16 (5/8"), M20 (3/4"), M22 (7/8")	
Brake	Capacity High strength torque shear bolt (HTB): M16, M20, M22 (5/8, 3/4, 7/8") Super (high) strength torque shear bolt (SHTB): M16, M20 (5/8, 3/4")
Anti-restart function	No load speed 17 min <sup>-1</sup>
Carrying Case	Max fastening torque 804 N·m (593 ft.lbs.) Sound pressure level 82 dB (A) Sound power level 90 dB (A) Vibration level 2.5 m/s <sup>2</sup> or less
	Dimensions w/ M22 Sleeve, w/ BL4020, BL4025: 255 x 95 x 334 mm (10 x 3-3/4 x 13-1/8") w/ M22 Sleeve, w/ BL4050F: 289 x 95 x 360 mm (11-3/8 x 3-3/4 x 14-1/8")
	Net weight 5.2 - 5.9 kg (11.5 - 13.0 lbs.)

Standard Equipment : - Screwdriver, Shoulder belt, Outer sleeve, Inner sleeve, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202310



Max. Torque shear bolt capacity  
**M22**



Lightweight

**5.5 kg**

battery: BL4040  
\* Without Sleeve



## Lightweight design



Reduces the stress on user's body in such a tough application as upward tightening of nut under steel beam.


## Higher maneuverability

Max. Torque shear bolt capacity  
**M22**

- High strength torque shear bolt (HTB): **M16, M20, M22**
- Super high strength torque shear bolt (SHTB): **M16, M20**
- A325 Torque shear bolt: **5/8, 3/4, 7/8"**
- A490 Torque shear bolt: **5/8, 3/4"**



Battery capacity warning lamp



**BL**  
MOTOR

High power with BL motor

WT001G



**5.5 kg**

battery: BL4040

Predecessor Model



**7.1 kg**

battery: BL1860Bx2

\* Without Sleeve

Large work amount

Fastening capacity of M22 Torque shear bolt:

battery: BL4025  
**Approx. 150 pcs**

battery: BL4040  
**Approx. 250 pcs**

Hook designed for use with shoulder belt to carry the tool

Shoulder belt (for transportation)



Bolt-tip ejection lever

enables easy ejection of removed bolt-tip left in the socket of the machine.



**XPT**

eXtreme Protection Technology

