



Random Orbit Polisher

PO5000C 125mm(5")

PO6000C 150mm(6")


Versatile one for various polishing operations

from scratch removal to fine finishing



Selectable 2 rotation modes

Rough Polishing




Forcible rotation mode

Orbital action with forced rotation of the pad for rough polishing such as scratch removal.



Fine Polishing



Free rotation mode

Orbital action with free rotation of the pad for fine polishing.

Thorough prevention measures for scratch-free car polishing

Tool rest with elastomer



Tool can be put upside down without damaging car body by tool rest with elastomer.

Turned up power supply cord



PO6000C
150 mm (6")



Detachable, rubber type vent dust cover

prevents wool fibers from entering into the motor.



PO5000C
125 mm (5")

Selectable maneuverability by applications

Front grip + Main grip



Easy to grip head not only for bonnet work but for sideway work

Side grip + Main grip



Side grip is available (option)

Main grip



Variable speed dial & trigger



Setting up RPM at full up position of trigger is easy by a variable speed dial. Variable speed control by trigger enables to adjust RPM during operation.

Accessories

Pad

(hook & loop type)



Size	Part No.	Part No. (EU)
100mm	197926-6	197925-8
125mm	197923-2	197922-4
150mm	197929-0	197928-2

Sponge pad

(hook & loop type)

(For wax coating)



Size	Part No.	Part No. (EU)
100mm	197912-7	197893-5
125mm	794558-6	-
150mm	197914-3	197894-3

Wool pad

(hook & loop type)

(For high gloss polishing)



Size	Part No.	Part No. (EU)
100mm	197918-5	197896-9
125mm	197920-8	197897-7

Felt pad

(hook & loop type)

(For removing wax)



Size	Part No.	Part No. (EU)
100mm	197916-9	197895-1
125mm	196152-4	-

Random Orbit Polisher

PO5000C 125 mm (5") / **PO6000C** 150 mm (6")

318

	PO5000C	PO6000C
Double Insulation	900W	900W
Variable Speed	125 mm (5")	150 mm (6")
Constant Speed	0 - 6,800	0 - 6,800
Soft Start	0 - 13,600	0 - 13,600
Hook & Loop	0 - 780	0 - 780
	0 - 780	0 - 780
	5.5 mm (7/32")	5.5 mm (7/32")
	Polishing: 6.5 m/s ²	Polishing: 7.0 m/s ²
	81 dB(A)	83 dB(A)
	92 dB(A)	94 dB(A)
	451x123x134mm	451x148x126mm
	(17-3/4"x4-7/8"x5-1/4")	(17-3/4"x5-7/8"x5")
	2.8 kg (6.2 lbs)	2.8 kg (6.2 lbs)
	4.0 m (13.1 ft)	4.0 m (13.1 ft)

Standard Equipment: Side grip (country-specific), Pad (country-specific), Hex Wrench

weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201706